

ActalisCodeSigner

ActalisCodeSigner is a command-line application that provides functionality for signing executable (**exe**, **msi**, **jar**) and script (**ps1**, **psd1**, **psm1**, **ps1xml**, **vbs**, **vbe**, **js**, **jse**, **wsf**) files by a code signing user.

Installation

ActalisCodeSigner is a portable application, you can install it by extracting the archive in any directory of your system.

This way you can interact with the application, from command line, by moving inside the directory where **ActalisCodeSigner** executable (**ActalisCodeSigner.exe** on Windows) is located and by launching the supported command.

Otherwise you can add the directory in **PATH** environment variable to use the tool from any position.

Usage

You can select different signature configuration by giving different input parameters.
In the examples we use short parameters for brevity.



Signature

Base signature mode is

```
ActalisCodeSigner.exe -fu username -fp password -in /path/to/fileToSign.exe
```

this way a signature is applied to *fileToSign.exe*

If you want to preserve the original file, you can specify output file path

```
ActalisCodeSigner.exe -fu username -fp password -in /path/to/fileToSign.exe -out /path/to/signedFile.exe
```

this way the signature is applied to *signedFile.exe* and the original file is left unaltered.



Signature with time stamp

With **ActalisCodeSigner** you can also apply a time stamp together with the signature

```
ActalisCodeSigner.exe -fu username -fp password -in /path/to/fileToSign.exe -ts  
-ts parameter indicate to apply time stamp with the signature. To use a different time stamp services  
from default (http://timestamp.actalis.com/) you can specify it after the parameter.
```

For example, if you want to use <https://url.tsa.com/> services (NB. this url is not related to a TSA services)

```
ActalisCodeSigner.exe -fu username -fp password -in /path/to/fileToSign.exe -ts  
https://url.tsa.com
```

If TSA services require authentication, you can provide credentials by **-tu** and **-tp** parameters

```
ActalisCodeSigner.exe -fu username -fp password -in /path/to/fileToSign.exe -ts  
https://url.tsa.com -tu username\_tsa -tp password\_tsa
```

2



Network configuration

ActalisCodeSigner supports connection to signing and time stamp services via proxy. Proxy configuration can be specified with **-pr**, **-pu** and **-pp** parameters

For example, with a proxy url <http://127.0.0.1>

```
ActalisCodeSigner.exe -fu username -fp password -in /path/to/fileToSign.exe -pr  
http://127.0.0.1 -pu username\_proxy -pp password\_proxy
```

If proxy is set at system level, you can provide **-pa** parameter to specify to look up the proxy automatically.

```
ActalisCodeSigner.exe -fu username -fp password -in /path/to/fileToSign.exe -pa
```

Other parameters

Below is the table with the exhaustive list of all supported parameters and a brief description.

NB. unless otherwise specified the parameters are optional

Short parameter	Full parameter	Description
-pm	--program-name	Additional signature field
-pr	--program-url	Additional signature field
-ts	--timestamp	Apply time stamp, if present, you can specify time stamp services url optionally
-fd	--fr-domain	Code signing domain
-fo	--fr-otp	Code signing OTP
-fp	--fr-password	Code signing password, mandatory parameter
-fr1	--fr-url1	Code signing services primary url
-fr2	--fr-url2	Code signing services secondary url
-fu	--fr-user	Code signing user name , mandatory parameter
-in	--input	File to sign path, mandatory parameter
-h	--help	Print guide
-pa	--proxy-auto	Proxy server configuration is searched automatically, if present
-pp	--proxy-password	Proxy server password
-pr	--proxy-url	Proxy server url
-pu	--proxy-user	Proxy server user name
-da	--digest-algorithm	Signature's digest algorithm, SHA-256 is used if not present Supported values are MD5, SHA1, SHA-256, SHA-384, SHA-512
-out	--output	Signed file path, signature is applied in place on input file if absent
-tp	--tsa-password	Time stamp services password, only used if --timestamp is also present
-tu	--tsa-user	Time stamp services user name, only used if --timestamp is also present